



Image shown may not
reflect actual package.

STANDBY

484 ekW 605 kVA

50 Hz 1500 rpm 400 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Low Fuel consumption

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested
- Flexible packaging options for easy and cost effective installation

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Cat dealers provide extensive post sale support including maintenance and repair agreements
- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT ® C18 ATAAC DIESEL ENGINE

- Utilizes ACERT™ Technology
- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic controlled governor

CAT GENERATOR

- Matched to the performance and output characteristics of Cat engines
- Load adjustment module provides engine relief upon load impact and improves load acceptance and recovery time
- UL 1446 Recognized Class H insulation

CAT EMCP 4 CONTROL PANELS

- Simple user friendly interface and navigation
- Scalable system to meet a wide range of customer needs
- Integrated Control System and Communications Gateway

STANDBY 484 ekW 605 kVA

50 Hz 1500 rpm 400 Volts



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none">• Light Duty Air Filter• Service indicator	<ul style="list-style-type: none"><input type="checkbox"/> Single element air filter<input type="checkbox"/> Dual element air filter<input type="checkbox"/> Heavy-duty dual element air filter with precleaner<input type="checkbox"/> Air inlet shut-off
Cooling	<ul style="list-style-type: none">• Radiator package mounted• Coolant level sight gauge• Coolant drain line with valve• Fan and belt guards• Cat® Extended Life Coolant*	<ul style="list-style-type: none"><input type="checkbox"/> Radiator duct flange<input type="checkbox"/> Low coolant level sensor
Exhaust	<ul style="list-style-type: none">• Dry exhaust manifold• Stainless steel exhaust flex fittings with split-cuff• Exhaust flange outlets	<ul style="list-style-type: none"><input type="checkbox"/> Industrial <input type="checkbox"/> Residential <input type="checkbox"/> Critical Mufflers<input type="checkbox"/> Manifold and turbocharger guards<input type="checkbox"/> Elbows and through-wall kits
Fuel	<ul style="list-style-type: none">• Primary fuel filter with integral water separator• Secondary fuel filters• Fuel priming pump• Fuel cooler* <p>*Not included with packages without radiators</p> <ul style="list-style-type: none">• Flexible fuel lines	<ul style="list-style-type: none"><input type="checkbox"/> Integral single wall fuel tank base<input type="checkbox"/> Manual transfer pump<input type="checkbox"/> Fuel level switch
Generator	<ul style="list-style-type: none">• Class H insulation• Class H temperature rise• VR6 voltage regulator with 3-phase sensing with load adjustment• IP23 Protection	<ul style="list-style-type: none"><input type="checkbox"/> Oversize generators<input type="checkbox"/> Internal excited (IE)<input type="checkbox"/> Permanent magnet excitation(PMG)<input type="checkbox"/> Cat digital voltage regulator (CDVR) with kVAR/PF control<input type="checkbox"/> Anti-condensation space heaters<input type="checkbox"/> Coastal Insulation Protection (CIP)<input type="checkbox"/> Reactive droop
Power Termination	<ul style="list-style-type: none">• Power Center houses EMCP controller and power/control terminations (rear mounted)• Circuit breaker, UL listed, 3 pole (80% & 100% Rated)• Circuit breaker, IEC compliant, 3-4 pole (100% Rated)• Segregated low voltage wiring termination panel• IP22 protection• Bottom cable entry	<ul style="list-style-type: none"><input type="checkbox"/> Power Center mounting option (right side)<input type="checkbox"/> Multiple circuit breaker options<input type="checkbox"/> C.B. Shunt trips<input type="checkbox"/> C.B. Auxiliary contacts
Governor	<ul style="list-style-type: none">• ADEM™ A4	<ul style="list-style-type: none"><input type="checkbox"/> Load Share Module
Control Panels	<ul style="list-style-type: none">• EMCP 4.1 (mounted in Power Center)• Speed adjustment• Voltage adjustment• Emergency stop pushbutton	<ul style="list-style-type: none"><input type="checkbox"/> EMCP 4.2<input type="checkbox"/> Local annunciator module (NFPA 99/110)<input type="checkbox"/> Remote annunciator module (NFPA 99/110)<input type="checkbox"/> Digital I/O module
Lube	<ul style="list-style-type: none">• Lubricating oil• Oil drain line with valves• Oil filter and dipstick• Fumes disposal• Lube oil level indicator• Oil cooler	<ul style="list-style-type: none"><input type="checkbox"/> Oil temperature sensor<input type="checkbox"/> Manual sump pump
Mounting	<ul style="list-style-type: none">• Formed steel narrow base frame• Linear vibration isolation-seismic zone 4	<ul style="list-style-type: none"><input type="checkbox"/> Oil skid base<input type="checkbox"/> Formed steel wide base frame
Starting/Charging	<ul style="list-style-type: none">• 24 volt starting motor• 24 volt, 45 amp charging alternator	<ul style="list-style-type: none"><input type="checkbox"/> Jacket water heater with shut-off valves<input type="checkbox"/> Engine block heater<input type="checkbox"/> Ether starting aid<input type="checkbox"/> Battery disconnect switch<input type="checkbox"/> Battery chargers (5 or 10 amp)<input type="checkbox"/> Oversize batteries<input type="checkbox"/> Batteries with rack and cables
General	<ul style="list-style-type: none">• Paint - Caterpillar yellow except rails and radiators gloss black• Flywheel housing - SAE No. 0	<ul style="list-style-type: none"><input type="checkbox"/> EU or CE Certificate of Conformance<input type="checkbox"/> Weather protective enclosure<input type="checkbox"/> Sound attenuated protective enclosure

STANDBY 484 ekW 605 kVA

50 Hz 1500 rpm 400 Volts



SPECIFICATIONS

CAT GENERATOR

Frame size..... LC6114G
Excitation..... Self Excitation
Pitch..... 0.6667
Number of poles..... 4
Number of bearings..... Single bearing
Number of Leads..... 012
Insulation..... UL 1446 Recognized Class H with
tropicalization and antiabrasion
- Consult your Caterpillar dealer for available voltages
IP Rating..... Drip Proof IP23
Alignment..... Pilot Shaft
Overspeed capability..... 150
Wave form Deviation (Line to Line)..... 2%
Voltage regulator..... Three phase sensing
Voltage regulation..... Less than +/- 1/2% (steady state)
Less than +/- 1/2% (w/ 3% speed change)
Telephone influence factor..... Less than 50
Harmonic Distortion..... Less than 5%

CAT DIESEL ENGINE

C18 ATAAC, I-6, 4-Stroke Water-cooled Diesel
Bore..... 145.00 mm (5.71 in)
Stroke..... 183.00 mm (7.2 in)
Displacement..... 18.13 L (1106.36 in³)
Compression Ratio..... 14.5:1
Aspiration..... Air-to-Air Aftercooled
Fuel System..... Electronic unit injection
Governor Type..... Caterpillar ADEM control system

CAT EMCP 4 SERIES CONTROLS

EMCP 4 controls including:

- Run / Auto / Stop Control
- Speed and Voltage Adjust
- Engine Cycle Crank
- 24-volt DC operation
- Environmental sealed front face
- Text alarm/event descriptions

Digital indication for:

- RPM
- DC volts
- Operating hours
- Oil pressure (psi, kPa or bar)
- Coolant temperature
- Volts (L-L & L-N), frequency (Hz)
- Amps (per phase & average)
- ekW, kVA, kVAR, kW-hr, %kW, PF (4.2 only)

Warning/shutdown with common LED indication of:

- Low oil pressure
- High coolant temperature
- Overspeed
- Emergency stop
- Failure to start (overcrank)
- Low coolant temperature
- Low coolant level

Programmable protective relaying functions:

- Generator phase sequence
- Over/Under voltage (27/59)
- Over/Under Frequency (81 o/u)
- Reverse Power (kW) (32) (4.2 only)
- Reverse reactive power (kVar) (32RV)
- Overcurrent (50/51)

Communications:

- Four digital inputs (4.1)
- Six digital inputs (4.2 only)
- Four relay outputs (Form A)
- Two relay outputs (Form C)
- Two digital outputs
- Customer data link (Modbus RTU) (4.2 only)
- Accessory module data link (4.2 only)
- Serial annunciator module data link (4.2 only)
- Emergency stop pushbutton

Compatible with the following:

- Digital I/O module
- Local Annunciator
- Remote CAN annunciator
- Remote serial annunciator

STANDBY 484 ekW 605 kVA

50 Hz 1500 rpm 400 Volts



TECHNICAL DATA

Open Generator Set - - 1500 rpm/50 Hz/400 Volts	DM9820	
Low Fuel Consumption		
Generator Set Package Performance Genset Power rating @ 0.8 pf Genset Power rating with fan	605 kVA 484 ekW	
Coolant to aftercooler Coolant to aftercooler temp max	49 ° C	120 ° F
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	122.8 L/hr 89.6 L/hr 62.4 L/hr	32.4 Gal/hr 23.7 Gal/hr 16.5 Gal/hr
Cooling System¹ Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	0.12 kPa 645 m³/min 81.8 L 20.8 L 61.0 L	0.48 in. water 22778 cfm 21.6 gal 5.5 gal 16.1 gal
Inlet Air Combustion air inlet flow rate	31.8 m³/min	1123.0 cfm
Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	555.1 ° C 93.7 m³/min 203 mm 10.0 kPa	1031.2 ° F 3309.0 cfm 8 in 40.2 in. water
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	160 kW 438 kW 75 kW 118 kW 30.3 kW	9099 Btu/min 24909 Btu/min 4265 Btu/min 6711 Btu/min 1723.2 Btu/min
Alternator² Motor starting capability @ 30% voltage dip Frame Temperature Rise	1227 skVA LC6114G 163 ° C	293 ° F
Lube System Sump refill with filter	38.0 L	10.0 gal
Emissions (Nominal)³ NOx mg/nm³ CO mg/nm³ HC mg/nm³ PM mg/nm³	3658.5 mg/nm³ 648.7 mg/nm³ 4.3 mg/nm³ 13.1 mg/nm³	

¹ For ambient and altitude capabilities consult your Cat dealer. Air flow restriction (system) is added to existing restriction from factory.

² Generator temperature rise is based on a 40° C (104° F) ambient per NEMA MG1-32. Some packages may have oversized generators with a different temperature rise and motor starting characteristics.

³ Emissions data measurement procedures are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations. Emissions data is based on 100% load and thus cannot be used to compare to EPA regulations which use values based on a weighted cycle.

STANDBY 484 ekW 605 kVA

50 Hz 1500 rpm 400 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, CSA, IEC60034-1, ISO3046, ISO8528, NEMA MG 1-22, NEMA MG 1-33, UL508A, 72/23/EEC, 98/37/EC, 2004/108/EC

Standby - Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046. Standby ambients shown indicate ambient temperature at 100% load which results in a coolant top tank temperature just below the shutdown temperature.

Ratings are based on SAE J1349 standard conditions. These ratings also apply at ISO3046 standard conditions. **Fuel rates** are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements, contact your Cat representative for details. For information regarding Low Sulfur fuel and Biodiesel capability, please consult your Cat dealer.

STANDBY 484 ekW 605 kVA

50 Hz 1500 rpm 400 Volts



DIMENSIONS

Package Dimensions		
Length	3933.9 mm	154.88 in
Width	1536.0 mm	60.47 in
Height	2167.2 mm	85.32 in
Weight	3968 kg	8,748 lb

NOTE: For reference only - do not use for installation design. Please contact your local dealer for exact weight and dimensions. (General Dimension Drawing #3206989).

Performance No.: DM9820

Feature Code: C18DE2Z

Gen. Arr. Number: 2476121

Source: European Sourced

June 13 2011

17806842

www.Cat-ElectricPower.com

© 2011 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress, as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.